



**Operating Wavelength Range:**

1260 to 1650nm

**Temp Range:** Operational -40 to 85°C

**Options:** Connectorized  
 Rack Mount  
 PON Module  
 Ribbon

**Optical Specifications**

Parameters	Unit	Specification
Operating Wavelength	nm	1260~1650
PDL	dB	≤ 0.25
PMD	ps	≤ 0.15
Return Loss	dB	≥ 55
Fiber Type		G657.A1

**Environmental Specifications**

Operation Temperature Range	°C	-40 - +85
Operation humidity	%	10 - 90
Power Handling	mW	300

**Loss Specifications**

Product Number	Split	Insertion Loss	Loss Uniformity	MMID
2-0014-07092-01	1 x 2	≤3.8 dBm	≤0.5 dB	1028496
CO- SPL-4N1	1 x 4	≤7.1 dBm	≤0.7 dB	-
CO- SPL-8N1	1 x 8	≤10.2 dBm	≤0.8 dB	-
CO- SPL-16N1	1 x 16	≤13.5 dBm	≤1.2 dB	-
CO- SPL-32N1	1 x 32	≤16.5 dBm	≤1.5 dB	-
CO- SPL-64N1	1 x 64	≤20.5 dBm	≤2.0 dB	-